Adgressor® & Adgressor® with EcoFlex™ System

Rider Scrubbers



FACT SHEET



Flexibility for every kind of clean.

The Advance Adgressor® rider-scrubber with EcoFlex™ System lets you clean green and still meet the highest expectations for clean floors. With the industry's most flexible floor-scrubber technology, you can develop a sustainable cleaning routine and quickly adjust to whatever the job demands. Be prepared to get more out of your budget, clean with less impact to the environment and maintain clean floors when you do.

Operators can quickly and easily select the right blend of pad pressure, water and detergent to tackle any cleaning challenge. Here are just a few of the flexible cleaning modes:

- Water Only Perfect for removing surface dirt and maintaining the clean look of floors. Water-only mode eliminates the impact of detergents on the environment and reduces cleaning costs.
- Ultra-low Detergent Well suited for routine cleaning where a small amount of green-certified detergent will do the trick. Water and detergent are dispensed separately at the scrub deck, eliminating solution waste.
- **Standard Detergent** The tough cleaning you expect. At standard detergent, pad pressure and flow rate, you'll have a combination powerful enough to pull stubborn dirt, grease, and oil from the surface.
- **Burst of Power** For deep, restorative cleaning or unexpected challenges. EcoFlex's burst of power temporarily increases your machine's pad pressure, detergent use and flow rate at the touch of a button.

The Adgressor is designed as a true industrial rider scrubber with reliability, productivity, and ease of use and maintenance built in. Combining large scrub decks and solution capacities with maneuverability and speed, the Adgressor delivers high productivity. A steel chassis and metal bumpers stand up to tough operating environments while thick high density polyethylene tanks will not dent, crack, or corrode.

The Adgressor with EcoFlex System delivers the flexibility to clean your floors more efficiently. By using a system that cleans like you do, you'll reduce your cost to clean and create a more sustainable cleaning program.

STANDARD FEATURES INCLUDE

- QuickChange[™] deck system
- 42 gallon solution and recovery tanks
- Smart Solutions™
- Powerful drive motor
- "One-Touch™" system activation
- Metal bumpers
- Comfortable, ergonomic design
- No-tools maintenance access
- Safe "Clear-View™" of cleaning area
- Best-in-class maneuverability
- Mechanical brake

TYPICAL APPLICATIONS INCLUDE

- Food and Beverage
- Distribution/Warehousing
- Manufacturing
- Large Retail/Malls
- Transportation Facilities
- Stadiums and Arenas
- Municipalities
- Universities
- Government Buildings




The Advance Adgressor®, designed with Total Clean™ Technology, is very comfortable and safe to use – by design. The result is increased productivity. The Advance Adgressor® is also designed with features to make it easy to clean up and maintain after cleaning. That reduces the total cost of ownership and drives down the cost of cleaning.



Adgressor® & Adgressor® with EcoFlex™ System


Rider Scrubbers




EcoFlex™ System models have One-Touch™ activation for an on-demand cleaning burst of power.



One-Touch™ activation of scrub system. All systems start and stop with machine motion.



The Advance Adgressor® can *Grow* with your company. The scrub deck interchangeability allows a larger, more productive scrub deck to be installed to address a growing company's increasing square footage.



The Advance Adgressor® turns within a 63 inch (160 cm) aisle. This improves productivity by allowing the Advance Adgressor® to easily clean smaller aisles than the competition.



Industrial Strength Solutions...

- Our products are designed using innovative technology that increases productivity and drives down the cost to clean.
- You can get expert service and maintenance for your Advance machines from factorytrained personnel around the world. Fast parts delivery, too.
- Maintain peak performance with Nilfisk Genuine OEM Parts.

Nilfisk Genuine OEM Parts

Technical Specifications

| Model | Adgressor® 2820 | Adgressor® 3220 | Adgressor® 3520 | Adgressor® 3820 | |
|----------------------------|---|---|------------------|------------------|--|
| Scrub Path | 28 in (71 cm) | 32 in (81 cm) | 35 in (89 cm) | 38 in (97 cm) | |
| Max. Productivity | 49,280 ft²/hr | 56,320 ft²/hr | 61,600 ft²/hr | 66,880 ft²/hr | |
| at 4.0 mph | | | | | |
| Max. Productivity | 30,800 ft²/hr | 35,200 ft²/hr | 38,500 ft²/hr | 41,800 ft²/hr | |
| at 2.5 mph | | | | | |
| Solution Tank | 42 gal (157 L) | 42 gal (157 L) | 42 gal (157 L) | 42 gal (157 L) | |
| Recovery Tank | 42 gal (157 L) | 42 gal (157 L) | 42 gal (157 L) | 42 gal (157 L) | |
| Brush Drive | | | | | |
| Disc – | 1.5 hp (1) | 1.5 hp (1) | 0.6 hp (3) | 0.6 hp (3) | |
| Cylindrical – | Two 0.75 hp, 560 Watt motors on opposing ends, poly-V belt brush drive – All Models | | | | |
| Scrub Deck | | | | | |
| Disc – | Manual-adjusting side skirts contain solution – All Models | | | | |
| Cylindrical – | Includes hopper for collecting small litter. Auto-adjusting side skirts contain solution – All Models | | | | |
| Brush Speed | | Disc 250 rpm, Cylindrical 900 rpm – All Models | | | |
| Brush Pressure | Programmable 3 settings up to 250 lb (113 kg) – All Models | | | | |
| Drive System | 1.5 hp motor with gear transmission, band brake and dynamic braking. Programmable | | | | |
| | speeds up to 4.5 mph (7.3 | speeds up to 4.5 mph (7.3 kph) – All Models | | | |
| Gradeability | Transport - 20% / 11.5 de | Transport - 20% / 11.5 deg., Working (scrubbing) - 8% / 4.6 deg – All Models | | | |
| Min. Turn-around | 63 inch (160 cm) on a machine with a 32 inch deck – All Models | | | | |
| Aisle Width | | | | | |
| Voltage | | 36 Volt for more power and longer run time – All Models | | | |
| Power Source | 305 Ah battery package with optional 395 Ah batteries – All Models | | | | |
| Battery Charger | Option of shelf or onboard charger – All Models | | | | |
| Solution Control | Smart Solutions™ is standar | Smart Solutions™ is standard providing better water and chemical utilization and fewer dump and refill cycles. – All Models | | | |
| Vacuum Motor | 0.75 hp 3-stage with optional dual vacuum – All Models | | | | |
| Sound Level | 68 dB A at operator's pos | 68 dB A at operator's position – All Models | | | |
| Frame Dimensions | Length = 61 in (155 cm), \ | Length = 61 in (155 cm), Width = 32 in (82 cm), Height = 53 in (135 cm) – All Models | | | |
| Squeegee Width | 32.6 in (83 cm) | 36.6 in (93 cm) | 42.1 in (107 cm) | 45.1 in (115 cm) | |
| Weight | Machine Only 657 lb (298 | Machine Only 657 lb (298 kg). With full tank and standard batteries 1,553 lb (705 kg) – All Models | | | |
| Optional Adgressor® EcoFle | x™ System Specifications | | | | |
| Solution Flow Pump | | | | | |
| Dilution Ratios | 32:1, 50:1, 64:1, 100:1, | 32:1, 50:1, 64:1, 100:1, 128:1, 150:1, 200:1, 256:1, 300:1 | | | |
| B CH 11 C | | | | | |

Specifications are subject to change without notice.



Refillable Cartridge Capacity 1.25 gal (4.75 L)

Battery Watering System

14600 21st Avenue North Plymouth, MN 55447-3408 www.advance-us.com Phone: 800-214-7700

800-989-6566

240 Superior Boulevard
Mississauga, Ontario, Canada L5T 2L2
www.nilfisk-advance.ca

Phone: 905-564-1149 or 800-668-8400 Fax: 905-564-1030 or 800-263-5111

