

AquaPLUS™ AXP™

Carpet Extractors



FACT SHEET



CRI Certified Extraction for a Deeper Clean.

The AquaPLUS™ AXP™ battery-powered walk-behind carpet extractors feature Advance's patented *LIFT*™ low-moisture technology for a clean that is CRI-certified. AquaPLUS extractors meet CRI seal of approval standards for soil removal and dry times in both *LIFT* and deep-cleaning restoration mode, giving you the confidence that your carpets will be truly clean and ready to use fast.

AquaPLUS extractors with *LIFT* (Low-moisture, Indirect spray, Fast dry time, True cleaning) feature a patented spray system for faster dry times. The single-spray nozzle design eliminates streaking and the possibility of water overlap that can lead to delayed drying. The fast dry time of the AquaPLUS extractors make them ideal solutions for daytime cleaning. No other extractors will give you that certified deep clean and get people back on your carpets in less than 30 minutes.

Extractors that receive the CRI Seal of Approval for deep cleaning extractors, have met the highest standards in the industry for their ability to remove soil and water and to preserve carpet appearance. The CRI-certified AquaPLUS extractors will help protect your carpet investment as well as meet green-cleaning standards outlined in the new GS-42 guidelines. The patented AXP system provides the flexibility to clean with any detergent, including those that are green certified. At just 69 dB A, AquaPLUS meets LEED-EB's IEQ credit guidelines for quiet operation. With *LIFT* technology and CRI-certification, the AquaPLUS extractors are the "greenest" carpet extractors in the industry.

The unique Deep Treat™ single-pass, pre-spray feature on the AquaPLUS AXP, eliminates clumsy hand-held spray bottles and allows the proper application of pre-spray chemical, minimizing chemical use and costs. Fast dry times, battery-operation, and a pre-spray feature contribute to increased productivity in your facility.

TYPICAL APPLICATIONS INCLUDE

- Hospitals / Healthcare Facilities
- Schools and Universities
- Churches and Religious Facilities
- Hotels
- Commercial Cleaning
- Government Buildings and Installations
- Airports, Train Stations, Bus Depots
- Casinos
- Office Buildings
- Health Clubs

STANDARD FEATURES INCLUDE

- Onboard Battery Charger
- Deep Treat™ Pre-Spray Mode (AXP™ model)
- *LIFT*™ Low Moisture Cleaning Mode
- Dual Counter Rotating Brushes
- Removable Debris Hopper
- Dual Laminar Flow Vacuum Shoes
- 250 Ah Batteries

OPTIONAL ACCESSORIES INCLUDE

- Anti Microbial Brushes
- 255 Ah AGM Batteries
- Tool Caddy
- Carrying Bag
- Electronic Float
- Battery Watering System



Advance AquaPLUS™ AXP™

Carpet Extractors



Dual laminar flow vac shoes allow for more efficient recovery of solution



Single touch button control sets proper operation of all functions. Simplifies training and consistent use by all operators



Tools-free removable brushes make for easy clean-up after use



Dual vac motors pull more water out of the carpet. Recovery tank lid design allows easy access to batteries



Defining Cleaning Innovation...

- Our products are designed using innovative technology that increases productivity and drives down the cost to clean.
- You can get expert service and maintenance for your Advance machines from factory-trained personnel around the world. Fast parts delivery, too.
- Maintain peak performance with Nilfisk Genuine OEM Parts.

Nilfisk Genuine OEM Parts

Technical Specifications

Solution System	
Solution Capacity	20 gal (76 L)
Solution Pump	100 psi diaphragm demand
Flow Rates	
Restoration Mode	0.81 gpm (3.1 L/min)
LIFT™ Mode	0.26 gpm (1 L/min)
Deep Treat™ Pre-Spray Mode	0.92 gpm (3.5 L/min)
Recovery Capacity	16 gal (61 L)
Vacuum System	
Vacuum Motor	Dual 3 stage bypass
Airflow	93 cfm (44 L/sec)
Waterlift	70 in H ₂ O (17.4 km/hr)
Vacuum Shoes	Dual 13.5 in (34 cm) Dual pivoting laminar flow 45 lb down pressure
Brush System	
Brushes	Dual 24 in (61 cm) Dual counter rotating with debris hopper
Brush Motors	Dual 1/2 horsepower permanent magnet
Brush Speed	950 RPM
Sound Level	69 dB A
Electrical System	24 V (4) X 6 V batteries
Batteries	250 Ah wet-acid (optional 255 Ah AGM)
Machine Speed	
Transport	220 ft/min (4 km/hr)
LIFT™ Mode	90 ft/min (1.6 km/hr)
Restoration Mode	50 ft/min (0.9 km/hr)
Light Deep Treat™ Mode	150 ft/min (2.7 km/hr)
Heavy Deep Treat™ Mode	100 ft/min (1.8 km/hr)
Coverage Rate	10,800 ft ² /hour (LIFT™ Mode) 6,000 ft ² /hour (Restoration Mode)
CRI Approval	Bronze for Deep Cleaning Extractors in both Restoration Mode and LIFT™ Mode
Machine Dimensions	L = 56 in (142 cm) x W = 27 in (69 cm) x H = 43.5 in (110 cm)
Machine Weight	650 lb (295 kg) with batteries / 370 lb (168 kg) without batteries
Shipping Weight	680 lb (308 kg)
Part Number	56 317 005 AquaPLUS™ AXP™ with 251 Ah wet batteries 56 317 007 AquaPLUS™ AXP™ with 255 Ah maint-free (AGM) batteries

Specifications are subject to change without notice.



Advance

14600 21st Avenue North
Plymouth, MN 55447-3408
www.advance-us.com
Phone: 800-850-5559
Fax: 800-989-6566

240 Superior Boulevard
Mississauga, Ontario, Canada L5T 2L2
www.nilfisk-advance.ca
Phone: 905-564-1149 or 800-668-8400
Fax: 905-564-1030 or 800-263-5111

©2012, Nilfisk-Advance, Inc.,
Printed in U.S.A., Form L1987A, 3-12

